

General Information

Extended Product Type:	XLP3-6BC
Product ID:	1SEP101975R0002
EAN:	7025840016991
Catalog Description:	630 A incl. 6 Bridge Clamps
Long Description:	XLP3-6BC

Categories

Products » Low Voltage Products and Systems » Fusegear » Fuse Switch Disconnectors » EasyLine

Ordering

EAN:	7025840016991
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363000

Dimensions

Product Net Width:	0.25 m
Product Net Height:	0.33 m
Product Net Depth:	0.142 m
Product Net Weight:	4.25 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.25 m
Package Level 1 Height:	0.33 m
Package Level 1 Length:	0.142 m
Package Level 1 Gross Weight:	4.25 kg
Package Level 2 EAN:	7025840016991

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
--------------	--

Additional Information

Degree of Protection:	acc. to IEC 60529 Front IP30
Frequency (f):	50/60 Hz
Fuse Protected Short-Circuit Making:	50 kiloampere rms
Fuse Protected Short-Circuit Withstand:	50 kiloampere rms
Fuse Size:	3
Fuse System:	DIN
Fuse Type:	NH
Handle Type:	detach
IIT Publishing Status:	Level 0 - Information enabled
Mounting Type:	Screwed
Number of Poles:	3
Product Main Type:	EasyLine
Product Name:	Fuse Switch Disconnecter
Rated Current (I _n):	Main Circuit 630 A
Rated Impulse Withstand Voltage (U _{imp}):	8 kV
Rated Operational Current AC-21B (I _e):	(690 V) 500 A
Rated Operational Current AC-22B (I _e):	(500 V) 630.0 A
Terminal Type:	Screw Terminals

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SEC312011B0202
Declaration of Conformity - CE:	1SEP500031P0001

Classifications

ETIM 4: EC001040 - Fuse switch disconnecter

ETIM 5: EC001040 - Fuse switch disconnecter

Object Classification Code: Q

UNSPSC: 39121600

