

General Information

Extended Product Type:	CT-ARS.11P
Product ID:	1SVR740120R3100
EAN:	4016779851695
Catalog Description:	CT-ARS.11P Time relay, true OFF-delay 1c/o, 24-240VAC/DC
Long Description:	The CT-ARS.11P is a single-function electronic time relay from the CT-S timer range. It provides an OFF-delay (true delay on break) function without auxiliary voltage and with 10 time ranges from 0.05 s to 300 h. This time relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 1 c/o (SPDT) output rated at 250 V / 4 A. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.

Additional Information

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +85 °C
Analog Inputs:	0
CCC Certificate:	CCC_2007010303255979
Connecting Capacity:	Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Connecting Capacity UL/CSA:	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG
Contact Rating UL/CSA:	B300
Country of Origin:	Germany (DE)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	2CDC111112D0201
Declaration of Conformity - CE:	1SVD981008-0000
Degree of Protection:	Housing IP50 Terminals IP20
E-number:	4033137
EAC Certificate:	EAC_RU_C-DE.ME77.B.02016
EAN:	4016779851695
EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / General
EPLAN Function Definition:	Coil / Coil, 2 connection points / Coil with drop-out delay A1_A2 Change-over contact / Change-over contact, 3 connection points / Change-over contact, off-delay 16_15_18
ETIM 4:	EC001439 - Timer relay
ETIM 5:	EC001439 - Timer relay
ETIM 6:	EC001439 - Timer relay
Electrical Durability:	AC-12 100000 cycle
Environmental Information:	1SAA981016-2401
Instructions and Manuals:	1SVC730010M0000
Invoice Description:	CT-ARS.11P Time relay, true OFF-delay 1c/o, 24-240VAC/DC
Maximum Operating Voltage UL/CSA:	Output Circuit 300 V AC
Mechanical Durability:	30000000 cycle
Minimum Order Quantity:	1 piece
Minimum Switching Capacity:	12 V 10 mA

Mounting Position:	Any
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Number of Digital Inputs:	0
Object Classification Code:	K
Output:	1 c/o (SPDT) contact
Overvoltage Category:	III
Package Level 1 EAN:	4016779851695
Package Level 1 Gross Weight:	0.122 kg
Package Level 1 Height:	109 mm
Package Level 1 Length:	30 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	97 mm
Pollution Degree:	3
Power Loss:	Approximately 2 W
Product Main Type:	CT-ARS
Product Name:	Time Relay
Product Net Depth:	103.7 mm
Product Net Height:	85.6 mm
Product Net Weight:	0.1 kg
Product Net Width:	22.5 mm
RMRS Certificate:	RMRS_1740021250
Rated Control Supply Voltage (U_s):	24 ... 240 V AC/DC
Rated Frequency (f):	50 Hz 60 Hz DC Hz
Rated Impulse Withstand Voltage (U_{imp}):	Input Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV
Rated Insulation Voltage (U_i):	Input Circuit / Output Circuit 500 V Output Circuit 1 / Output Circuit 2 300 V
Rated Operational Current AC-12 (I_a):	(230 V) 4 A
Rated Operational Current AC-15 (I_a):	(230 V) 3 A
Rated Operational Current DC-12 (I_a):	(24 V) 4 A
Rated Operational Current DC-13 (I_a):	(24 V) 1.5 A
Regulatory Compliance Mark (RCM):	Yes
RoHS Date:	1146
RoHS Information:	1SVD981001-4400
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	CT-ARS.11P Time relay, true OFF-delay
Short-Circuit Protective Devices:	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Standards:	IEC/EN 61812-1 UL 508 CAN/CSA C22.2 No.14
Terminal Type:	Screwless Terminals
Time Range:	0.05 s - 10 min
Timer Relay Type:	True OFF-Delay
Wire Stripping Length:	8 mm
cULus Certificate:	cULus508_20110711-E140448A
eClass:	7.0 27371790

