

316BP6



Products → Low Voltage Products and Systems → Industrial Plugs and Sockets → Basic & Safe

General Information

Extended Product Type:	316BP6
Product ID:	2CMA102164R1000
EAN:	7392696021647
Catalog Description:	Ind. P&S#316BP6
Long Description:	4x16A / IP 44 - Plug Clock Position Of Grounding Contact 6 hour Color code Red

Ordering

EAN:	7392696021647
-------------	---------------

Minimum Order Quantity:	10 piece
--------------------------------	----------

Country of Origin:	Turkey (TR)
---------------------------	-------------

Dimensions

Product Net Width:	53 mm
---------------------------	-------

Product Net Height:	53 mm
----------------------------	-------

Product Net Length:	129 mm
----------------------------	--------

Product Net Depth:	129 mm
---------------------------	--------

Product Net Weight:	0.168 kg
----------------------------	----------

Container Information

Package Level 1 Width:	150 mm
-------------------------------	--------

Package Level 1 Length:	280 mm
--------------------------------	--------

Package Level 1 Height:	225 mm
--------------------------------	--------

Package Level 1 Gross Weight:	1.863 kg
--------------------------------------	----------

Package Level 1 EAN:	7392696036443
-----------------------------	---------------

Package Level 1 Units:	10 piece
-------------------------------	----------

Additional Information

Additional Information:	3P+E
--------------------------------	------

Cable Cross-Section:	1 ... 2.5 mm ²
-----------------------------	---------------------------

Color:	Red
---------------	-----

Connection Type:	Screw clamp
-------------------------	-------------

Degree of Protection:	IP44
------------------------------	------

Enclosure Material:	Plastic (PA)
----------------------------	--------------

Frequency (f):	50 Hz 60 Hz
Housing Material:	Plastic (PA)
Invoice Description:	Ind. P&S#316BP6
Number of Poles:	4
Product Main Type:	BP
Product Name:	Plug
Protection Type:	Watertight
Rated Current (I_n):	16 A
Rated Voltage (U_r):	380 ... 415 V
Standards:	IEC 60309-1 IEC 60309-2

Classifications

eClass:	27440501
UNSPSC:	39120000

